

# blueplanet 50.0 TL3

Transformerless, three-phase string inverter.



The inverter you can count on.

Compact wall-mounted unit for decentralised megawatt projects

Tailored for economical use in solar parks

Special properties for extreme climatic conditions

Farsighted technical features for future requirements

Installation-friendly connection area, user-friendly operation

Integrated section switches for cost-effective grid and plant protection with Powador-protect



## Technical Data

| <b>DC input data</b>                           |  | <b>50.0 TL3</b>   |
|--|--|---|
| Max. recommended PV generator power            |  | 70 000 W  |
| MPP range                                      |  | 580 <sup>1)</sup> – 900 V   |
| Operating range                                |  | 580 <sup>1)</sup> – 1 050 V   |
| Rated DC voltage / start voltage               |  | 600 V / 670 V   |
| Max. no-load voltage                           |  | 1 100 V   |
| Max. input current                             |  | 90 A  |
| Max. short circuit current I <sub>sc max</sub> |  | 190 A   |
| Number of MPP tracker                          |  | 1   |
| Connection per tracker                         |  | S / B / M: 1; XL: 10  |
| <b>AC output data</b>                          |  |   |
| Rated output                                   |  | 50 000 VA   |
| Max. power                                     |  | 52 000 VA   |
| Line voltage                                   |  | 240 V / 415 V (3 / N / PE; 3 / PEN)<br>230 V / 400 V (3 / N / PE; 3 / PEN)<br>220 V / 380 V (3 / N / PE; 3 / PEN) |
| Voltage range (Ph-Ph)                          |  | 305 – 480 V   |
| Rated frequency (range)                        |  | 50 Hz / 60 Hz (42 – 68 Hz)  |
| Rated current                                  |  | 3 x 69.6 A @ 415 V<br>3 x 72.2 A @ 400 V<br>3 x 76.0 A @ 380 V  |
| Max. current                                   |  | 3 x 76.5 A  |
| Reactive power / cos phi                       |  | 0 - 100 % Snom / 0.30 ind. – 0.30 cap.  |
| Max. total harmonic distortion (THD)           |  | 1.6 %   |
| Number of grid phases                          |  | 3   |
| <b>General data</b>                            |  |   |
| Max. efficiency                                |  | 98.5 %  |
| Europ. efficiency                              |  | 98.1 %  |
| CEC efficiency                                 |  | 98.0 %  |
| Standby consumption                            |  | 2.5 W   |
| Circuitry topology                             |  | transformerless   |
| <b>Mechanical data</b>                         |  |   |
| Display  |  | graphical display + LEDs  |
| Control units                                  |  | 4-way navigation + 2 buttons  |
| Interfaces                                     |  | Ethernet, USB, RS485, optional: 4-DI  |
| Fault signalling relay                         |  | potential-free NOC max. 30 V / 1 A  |
| DC connection                                  |  | S / B / M: max.120 mm <sup>2</sup> cable plug, Cu / Al<br>XL: DC plugs (SUNCLIX)                                  |
| AC connection                                  |  | screw terminals, max. 95 mm <sup>2</sup> , Cu / Al  |
| Ambient temperature                            |  | -20 °C – +60 °C <sup>2)</sup>   |
| Humidity                                       |  | 0 – 100 %   |
| Max. installation elevation (above MSL)        |  | 3 000 m   |
| Min. distance from coast                       |  | 2 000 m / 500 m (OD+ version)   |
| Cooling  |  | temperature controlled fan  |
| Protection class                               |  | IP65  |
| Noise emission                                 |  | < 61 db (A)   |
| H x W x D                                      |  | 760 x 500 x 425 mm  |
| Weight   |  | 70 kg (S), 71 kg (B / M), 73 kg (XL)  |
| <b>Certifications</b>                          |  |   |
| Safety   |  | IEC 62109-1/-2, EN 61000-6-1/-2/-3, EN 61000-3-11/-12   |
| Grid connection rule                           |  | overview see homepage / download area   |

<sup>1)</sup> 560 V @ 220 V / 380 V; 610 V @ 240 V / 415 V  
<sup>2)</sup> Power derating at high ambient temperatures

| <b>Versions</b>              | <b>S</b> | <b>B</b> | <b>M</b> | <b>XL</b>  | <b>XLF</b> |
|------------------------------|----------|----------|----------|------------|------------|
| Number of DC inputs          | 1        | 1        | 1        | 10         | 10         |
| DC switch                    | -        | ✓        | ✓        | ✓          | ✓          |
| Fuse holder PV+ without fuse | -        | -        | -        | ✓          | ✓          |
| String protection PV -       | -        | -        | -        | ○          | ○          |
| DC surge protection          | -        | -        | ○        | Type 1 + 2 | Type 1 + 2 |
| AC surge protection          | -        | -        | ○        | ○          | ○          |
| OD+                          | ★        | ★        | ★        | ★          | ★          |

standard = ✓ upgradeable = ○ optional = ★